

## MATERIALS DATA SHEET:

**Product Name**: EG- 2C NN(Natural Net) **Manufacturer:** Ero-Guard, Inc. **Contact:** Brian F Dingels (612) 382-2783

## **Physical Description:**

Size: Available in 16' and 8' widths and 112.5' and 562.5' lengths (Custom cuts are available upon request).

<u>Netting</u>: **Top net-**The netting is made from fully biodegradable organic jute fiber, that is LENO weaved for a higher quality product, 1.0" x 0.5" opening.

**Bottom net-** The netting is made from fully biodegradable organic jute fiber, that is LENO weaved for a higher quality product, 1.0" x 0.5" opening.


Thread: Biodegradable yarn, that is in a stitching pattern of 1.5"x 2.0".

Matrix: 100% Pure coconut fibers,  $0.50 \text{ lbs/yd}^2$ 


<u>Packaging</u>: All rolls are wrapped tightly with stretch wrap to protect the rolled erosion control product from the weather and elements.

**Specification Notes:** EG-2C NN(Natural Net) is made to conform to guidelines set by the ECTC (Erosion Control Technology Council) and by FHWA (Federal Highway Association) as an extended term erosion control blanket.

- **Recommended Applications:** EG-2C NN(Natural Net) is an extended term erosion control blanket that is designed to have a function longevity of up to 24 months (Longevity may vary based upon environmental conditions). This product is recommended for use on slopes up to 2:1-1:1 and in medium flow channels.
- **Recommended Installation pattern:** The leading edge is to be trenched into a 6" deep trench and the blanket is to be placed parallel to the anticipated water flow. When more than 1 blanket is required, they are to be overlapped 6" on all overlapping sides and tiled in a shingle type pattern as to not let the water underneath the blanket.




4:1 SLOPES



3:1 SLOPES

1.75 staples/yd<sup>2</sup>

2:1 SLOPES



3.5 staples/yd<sup>2</sup> MED. to HIGH FLOW CHANNEL



X XX

## **Your Leader In Erosion Control Blankets**

412 Hwy 22 South · Mapleton, MN · 56065 Phone: (612) 382-2783 · Fax: (507) 524-3859